



#### Imperial dimensions

Ratings	20' Standard	40' Standard	40' HC Standard	45' HC Dry	40' HC Refrigerated
Standard Payload on HWY	38,000 lb.	44,400 lb.	44,000 lb.	43,000 lb.	42,000 lb.
Tare Weight	4,850 lb.	8,168 lb.	8,587 lb.	10,450 lb.	10,141 lb.
<b>External Dimensions</b>					
Length	19'-10"	40'-0"	40'-0"	45'-0"	40'-0"
Width	8'-0"	8'-0"	8'-0"	8'-0"	8'-0"
Height	8'-6"	8'-6"	9'-6"	9'-6"	9'-6"
<b>Internal Dimensions</b>					
Length	19'-4"	39'-5"	39'-5"	44'-6"	38'-0"
Width	7'-8"	7'-8"	7'-8"	7'-9"	7'-6"
Height	7'-9 7/8"	7'-9 7/8"	8'-9 7/8"	8'-10"	8'-4"
<b>Door Opening</b>					
Width	7'-8"	7'-8"	7'-8"	7'-8"	7'-6 2/10"
Height	7'-5 5/8"	7'-5 5/8"	8'-5"	8'-6"	8' - 4 7/10"
<b>Cube</b>			Cargo Access Height		8' - 2 8/10"
Cubic Capacity	1,166 ft. <sup>3</sup>	2,377 ft. <sup>3</sup>	2,681 ft. <sup>3</sup>	3,055 ft. <sup>3</sup>	2,383 ft. <sup>3</sup>

#### Metric Dimensions

Ratings	20' Standard	40' Standard	40' HC Standard	45' HC Dry	40' HC Refrigerated
Standard Payload on HWY	17,235 kg	20,140 kg	19,960 kg	19,500 kg	19,050 kg
Tare Weight	2,200 kg	3,700 kg	3,890 kg	4,740 kg	4,600 kg
<b>External Dimensions</b>					
Length	6,058 mm	12,192 mm	12,192 mm	13,716 mm	12,192 mm
Width	2,438 mm	2,438 mm	2,438 mm	2,438 mm	2,438 mm
Height	2,591 mm	2,591 mm	2,896 mm	2,896 mm	2,896 mm
<b>Internal Dimensions</b>					
Length	5,900 mm	12,025 mm	12,025 mm	13,556 mm	11,583 mm
Width	2,348 mm	2,348 mm	2,348 mm	2,352 mm	2,294 mm
Height	2,385 mm	2,385 mm	2,690 mm	2,701 mm	2,545 mm
<b>Door Opening</b>					
Width	2,340 mm	2,340 mm	2,340 mm	2,340 mm	2,290 mm
Height	2,275 mm	2,275 mm	2,578 mm	2,588 mm	2,557 mm
<b>Cube</b>			Cargo Access Height		2,509 mm
Cubic Capacity	33.04 m <sup>3</sup>	67.34 m <sup>3</sup>	75.95 m <sup>3</sup>	86.5 m <sup>3</sup>	67.5 m <sup>3</sup>